




LondonStone™ has put quality and affordability back into landscaping.

- No concrete footings required, easy to install
- No mortar necessary
- Durable, structurally stable walls
- No maintenance, environmentally safe
- Less costly than name-brand retaining walls
- Safe, comfortable integral step unit
- Lip system, preferred by landscapers
- Quality, clean, consistent units available in ten colors



7" LondonStone
7 x 16 x 12
Weight: 75 lbs.
Face Area: .78 sq. ft
Units per Cube: 27



7" LondonStone Cap
7 x 16 x 12
Weight: 75 lbs.
Face Area: .78 sq. ft
Units per Cube: 27




7" Straight Face
7 x 18 x 12
Weight: 80 lbs.
Face Area: .88 sq. ft
Units per Cube: 27



4" Round Cap
4 x 16 x 12
Weight: 50 lbs.
Face Area: .44 sq. ft
Units per Cube: 54



Reversible Cap
3-1/2 x 13 x 12
Weight: 37 lbs.
Face Area: .31 sq. ft
Units per Cube: 72



Step Unit
7 x 16 x 20
Weight: 168 lbs.
Face Area: .78 sq. ft
Units per Cube: 12



Half Step
7 x 8 x 20
Weight: 84 lbs.
Face Area: .39 sq. ft
Units per Cube: 24






Decrowall
4 x 12 x 8
Weight: 25 lbs.
Face Area: .33 sq. ft
Units per Cube: 96



Decrowall Cap
4 x 12 x 8
Weight: 25 lbs.
Face Area: .33 sq. ft
Units per Cube: 96



Reversible Decrowall Cap
2-5/8 x 8 x 8
Weight: 10 lbs.
Face Area: .14 sq. ft
Units per Cube: 208



All the benefits of LondonStone™ plus...


- Three different sizes for added versatility
- The natural/rough look of Rugged LondonStone blends with the environment and withstands the effects of it.
- Available in natural blended colors



Rugged LondonStone is packaged as one unit in three different sizes. Rugged Cap is sold separately.



Rugged Cap
3-1/2 x 13 x 12
Weight: 37 lbs.
Face Area: .31 sq. ft
Units per Cube: 72



6" Rugged
7 x 6 x 12
Weight: 35 lbs.
Face Area: .29 sq. ft





12" Rugged
7 x 12 x 12
Weight: 68 lbs.
Face Area: .58 sq. ft

18" Rugged
7 x 18 x 12
Weight: 79 lbs.
Face Area: .88 sq. ft



Rugged units
total
23.62 sq. ft.
per pallet





LondonLite™ provides quality “in-block” lighting solutions.

- An affordable landscape lighting alternative
- Low voltage lighting system designed into all of our block sizes & colors
- Safety feature of having a wall lit stairway or walkway
- Easy maintenance with a screw in lens cap on the front of the block



Grid Lip is the solution to building retaining walls over five feet tall.

- Easy installation
- Available in 7" LondonStone and 7" Straight Face
- Geogrid easily slips into the teeth of the block by pulling up on the grid behind the wall.
- Geogrid does not need to bend around the lip of the block thus increasing the design strength.



LONDONSTONE INSTALLATION GUIDELINES

Step 1: ESTIMATE NUMBER OF UNITS

- A) Figure square footage of retaining wall (length of wall x height of wall = total sq. ft.)
- B) Divide total sq. ft. of wall by sq. ft. face area of unit = Total units needed
 Example: Wall needed is 15' long x 4' high: 15 x 4 = 60 sq. ft.
 Using 7" LondonStone; face area = .78 sq. ft. 60 ÷ .78 sq. ft. = 77 units

Step 2: PREPARE BASE

Place a leveling pad using 1/2" - 3/4" crushed stone, recycled concrete or gravel, approx. 6" thick depending on the height of the wall. Compact to form a consistent level base.

Step 3: INSTALL THE BASE COURSE

Start at the lowest elevation. Place and level each of the first course units side to side, front to back and with the adjacent unit.

Step 4: BACKFILL

Install 12" of drainage fill (3/4" rock) behind each course. Compact these materials with a hand tamper or vibrating plate compactor.

Step 5: INSTALL ADDITIONAL COURSES

Position the second course of LondonStone upon the preceding layer straddling the two lower units and staggering the vertical joints.



Manufactured by:
 Concrete Products of New London
 Alexandria Concrete Company

320-354-2311 New London
 320-589-3700 Morris
 320-763-4600 Alexandria
 218-631-1558 Wadena
 763-295-3122 Monticello

Visit us online at: www.LondonStone.net