



Granite



Buff



River Rock



Autumn

Take control of storm water management!

Environmentally friendly London Permeable Pavers are the perfect solution for putting the drain on unwanted water run-off.

- Removes storm water fast without sloping the landscape and allows 4" of rain water to drain per hour through a correctly installed subbase
- Two paver sizes (6" X 6" and 4" X 6"), with four blended colors on a Euro cobble contoured face
- Provides natural filtration process where pollutants are removed and broken down by natural bacteria found in aggregate bed.
- Reduction of runoff by as much as 100% from frequent, low intensity and short duration storms
- Reduces project development costs by a reduction of storm sewer and drainage equipment and saves space on job site
- Exceeds ASTM Specifications for permeable pavers at 12.1% voids



Buff Blend Permeable Paver



Buff Blend pictured

Patent Pending

PERMEABLE PAVER STANDARD DRAINAGE SYSTEM



Call today for more information: 1-800-450-3122

We've opened up more possibilities!

LondonPaver Permeable Pavers are the perfect solution for storm water management. Our patent pending environmentally friendly pavers naturally filter out water impurities and deliver the water back to the water table, not the storm drain.

We've opened up more possibilities with four blended colors and two sizes. Our Permeable Pavers have also surpassed the Americans Disability Act (ADA) standards for traffic slip resistance.

Whether your design requires a simple sidewalk or an entire roadway, LondonPaver Permeable Pavers are up to the task.



Granite Blend Permeable Paver



Buff Blend Permeable Paver

PERMEABLE PAVER SPECIFICATIONS

Permeable Pavers	4" x 6"	6" x 6"	Totals
Thickness	3.125"	3.125"	
Square Feet/piece	.167	.25	
Pieces/pallet	192	96	= 288
Each Band Contains	24 pcs	12 pcs	= 36
Bands/ pallet			8
Sq.Ft./ band	4	3	= 7 sq. ft.
Sq. Ft. / pallet	32	24	= 56 sq. ft.

- 12.1% total surface area of permeability
- Meets and/or exceeds requirements of ASTM C936
- Meets International Concrete Paver Institute (ICPI) guidelines for permeable pavers

Permeable pavers are palletized in a 2:1 ratio of 4" x 6" to 6" x 6"

Colors shown are illustrated as accurately as possible. Due to the nature of the product and the variations in printing, we suggest that you look at actual samples to make your color choice. All Pavers meet or exceed requirements of ASTM C-936 for compression, absorption and dimension specifications.



Manufactured by:
Concrete Products of New London
Alexandria Concrete Company

320-354-2311 New London
320-589-3700 Morris
320-763-4600 Alexandria
218-631-1558 Wadena
763-295-3122 Monticello
320-587-3334 Hutchinson

**Contact us today for more information:
1-800-450-3122 • www.LondonPaver.net**