

# LondonPaver™

Beauty Designed To Last



---

COBBLESTONE • RECTANGLE • CIRCLE • PARAGON

---



## Cobblestone Paver

A Timeless Classic



3-1/8" x 6-1/4"



6-1/4" x 6-1/4"



6-1/4" x 9-3/8"





## Circle Pavers

Unique & Flexible



Center Pac



Large Wedge



6-1/4" x 6-1/4"



3-1/8" x 6-1/4"



## Rectangle Paver

Tradition with Style





# Paragon Paver

Elegantly Unique



Paver Specs.	Rectangle		Paragon		Cobblestone	
	3" X 6"	6" X 6"	6" X 6"	6" X 6"	6" X 9"	Large Wedge
Width	7-7/8"	9"	6-1/4"	6-1/4"	9-3/8"	6-1/2"
Height	3-7/8"	5-1/2"	3-1/8"	6-1/4"	6-1/4"	6"
Thickness	2-3/8"	2-3/8"	2-3/8"	2-3/8"	2-3/8"	2-3/8"
Sq. Ft. per Pallet	96	90	52.5	78.75	84.38	81
Sq. Ft. per Piece	.22	.29	.125	.25	.375	.214
Sq. Ft. per Band	16	18	7.5	11.25	16.88	11.57
Pieces Per Sq. Ft.	4.5	3.45	8	4	2.66	4.68
Pieces per Band	72	63	60	45	45	54
Bands per Pallet	6	5	7	7	5	7
Pieces per Pallet	432	315	420	315	225	378
Pounds per Piece	6	7.5	3.56	7.36	11.16	6.10
Pounds per Pallet	2592	2363	1535	2359	2551	2306


## LondonPaver Color Varieties

Choose from four natural colors and five blends. The Cobblestone series is only available in blended colors.



Colors shown are illustrated as accurately as possible. Due to the nature of the product and the variations in printing, we suggest that you look at actual samples to make your color choice. All Pavers meet or exceed requirements of ASTM C-936 for compression, absorption and dimension specifications.

## Pattern Options



## LONDONPAVER INSTALLATION GUIDELINES

- Excavate unsuitable, unstable or unconsolidated subgrade material and compact the area which has been cleared. Backfill and level with class 5 gravel or recycled concrete suitable for base material of compacted base for light vehicular and pedestrian traffic, increasing to 12 in. for heavy vehicular and industrial use.
- Place bedding course of washed concrete and sand conforming to the grading requirements to an approx. depth of 1 to 1-1/2".
- Where required, cut pavers with a concrete saw to fit accurately, neatly and without damaged edges.
- Tamp pavers with a plate compactor uniformly level, true to grade and free of movement.
- Fill joints with sand.

## Circle Paver Specs.

Ring	Diameter (ft.)	Square Feet	Center	Small Wedge	Medium Wedge	Large Wedge	Cum. Large W.	6-1/4" X 6-1/4"	Cum. 6" X 6"	3-1/8" X 6-1/4"	Cum. 3" X 6"
0			4								
1				8							
2	2.5	4.9			14						
3	3.5	9.6				18	18				6
4	4.7	17.1				13	31	13	13		7
5	5.8	26.7				16	47	16	29	3	10
6	6.8	36.7				20	67	20	49	1	11
7	8.0	50.2				23	90	23	72	2	13
8	9.0	63.6				27	117	27	99		13
9	10.2	81.1				30	147	30	129	1	14
10	11.2	97.9				33	180	33	162	3	17
11	12.3	119.4				37	217	37	199		17
12	13.3	139.6				40	257	40	239	1	18
13	14.3	161.3				43	300	43	282	2	20
14	15.4	186.6				46	346	46	328	3	23
15	16.5	213.7				50	396	50	378		23
16	17.7	245.0						99	477	1	24
17	18.7	273.5						106	583		24
18	19.8	306.2						112	695		24
19	20.8	340.7						118	813	1	25

Center pack is sold as one banded unit which includes the center piece and the first two rings. It covers 4.9 sq./ft. Circle pavers are only available in the Cobblestone blended colors.



Manufactured by:  
Concrete Products of New London  
Alexandria Concrete Company

320-354-2311 New London  
320-589-3700 Morris  
320-763-4600 Alexandria  
218-631-1558 Wadena  
763-295-3122 Monticello

Visit us online at: [www.LondonPaver.net](http://www.LondonPaver.net)